



*No Hassle Compression*

### CC100 – 100 HP

		DISCHARGE PRESSURE (psig)										
		60	80	100	120	140	160	180	200	220	240	250
SUCTION	2	665	662	660	585	575	500	495	425	400	395	390
	5	800	795	690	680	675	555	550	530	495	480	475
	10	1020	1015	880	715	705	700	695	590	545	525	520
	20		1060	1050	885	875	735	720	720	685	625	620
	30			1040	1040	990	830	825	810	745	735	710
	40			1180	1180	1180	1025	1015	825	810	760	720
	50				1230	1230	1230	1215	975	965	950	900
	60					1140	1140	1140	1115	1100	1080	1060
	70						1300	1300	1300	1280	1250	1230

Pressures in PSIG Flow Rates in MSCFD  
 Performance based on 2500 ft, gas density .665, ambient temp 68°F  
 using Enduro G-2 V2 Selector Program

## CC100

### Standard Features

- Compressor – Gardner Denver Enduro 25
- Driver – Cummins G8.3
- Weight – 9,000 lb/4,080 kg
- Compressor Speed Optimization

### Options

- CPC Controller
- Sound Proofing
- Metering
- SCADA Output
- Blowcase
- Fire & Gas Detection



Phone: (403) 219-3026  
 Fax: (403) 717-1759

#8, 1820 – 30<sup>th</sup> Ave NE  
 Calgary, Alberta Canada T2E 7M5

info@compactcompression.com