



No Hassle Compression

CC50 – 50 HP

| SUCTION | DISCHARGE PRESSURE (psig) | | | | | | | | | | HP OPTION | | |
|---------|---------------------------|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----------|-----|-----|
| | 60 | 80 | 100 | 120 | 140 | 160 | 180 | 200 | 220 | 240 | 260 | 280 | 300 |
| | 2 | 354 | 349 | 307 | 303 | 257 | 253 | 248 | 206 | 194 | 185 | 177 | |
| 5 | 420 | 415 | 365 | 360 | 305 | 300 | 295 | 245 | 230 | 220 | 210 | 200 | 190 |
| 10 | 525 | 460 | 390 | 388 | 385 | 325 | 323 | 320 | 300 | 235 | 225 | 215 | 210 |
| 20 | | 650 | 560 | 475 | 470 | 390 | 385 | 380 | 375 | 285 | 275 | 265 | 250 |
| 30 | | 720 | 720 | 620 | 520 | 510 | 425 | 420 | 415 | 320 | 305 | 290 | 280 |
| 40 | | | 765 | 765 | 650 | 540 | 525 | 515 | 425 | 410 | 390 | 375 | 360 |
| 50 | | | | 905 | 770 | 625 | 620 | 520 | 515 | 505 | 415 | 400 | 390 |
| 60 | | | | | 900 | 750 | 730 | 605 | 590 | 495 | 490 | 480 | 465 |
| 70 | | | | | | 860 | 715 | 705 | 690 | 575 | 560 | 545 | 530 |

Pressures in PSIG Flow Rates in MSCFD
 Performance based on 2500 ft, gas density .665, ambient temp 68°F
 using Enduro G-2 V2 Selector Program

CC50

Standard Features

- Compressor – Gardner Denver Enduro 12
- Driver – GM 5700
- Weight – 5,500 lb/2,500 kg
- Compressor Speed Optimization

Options

- CPC Controller
- Sound Proofing
- Metering
- SCADA Output
- Blowcase
- Fire & Gas Detection



Phone: (403) 219-3026
 Fax: (403) 717-1759

#8, 1820 – 30th Ave NE
 Calgary, Alberta Canada T2E 7M5

info@compactcompression.com