



*No Hassle Compression*

### CC75 – 75 HP

		DISCHARGE PRESSURE (psig)										
		60	80	100	120	140	160	180	200	220	240	250
SUCTION	5	670	570	565	485	480	475	390	375	345	340	335
	10	840	720	620	610	505	500	495	490	390	385	375
	20	870	870	735	625	620	615	500	495	475	440	435
	30		810	810	810	680	675	670	580	550	510	495
	40			990	990	830	820	710	705	535	520	510
	50				1030	1030	1030	870	855	680	650	620
	60					980	980	980	800	785	775	760
	70						930	930	915	900	880	

Pressures in PSIG Flow Rates in MSCFD  
 Performance based on 2500 ft, gas density .665, ambient temp 68°F  
 using Enduro G-2 V2 Selector Program

## CC75

### Standard Features

- Compressor – Gardner Denver Enduro 25
- Driver – GM 5700 or Cummins G5.9
- Weight – 8,000 lb/3,625 kg
- Compressor Speed Optimization

### Options

- CPC Controller
- Sound Proofing
- Metering
- SCADA Output
- Blowcase
- Fire & Gas Detection



Phone: (403) 219-3026  
 Fax: (403) 717-1759

#8, 1820 – 30<sup>th</sup> Ave NE  
 Calgary, Alberta Canada T2E 7M5

info@compactcompression.com