



*No Hassle Compression*

## CC75 - 75 HP

DISCHARGE PRESSURE (psig)

SUCTION	DISCHARGE PRESSURE (psig)										
	60	80	100	120	140	160	180	200	220	240	250
5	670	570	565	485	480	475	390	375	345	340	335
10	840	720	620	610	505	500	495	490	390	385	375
20	870	870	735	625	620	615	500	495	475	440	435
30		810	810	810	680	675	670	580	550	510	495
40			990	990	830	820	710	705	535	520	510
50				1030	1030	1030	870	855	680	650	620
60					980	980	980	800	785	775	760
70						930	930	915	900	880	

• Pressures in PSI • Flow Rates in MSCFD

\*Performance based on 2500 ft, gas density .665, temp 68 °F using Enduro G-2 V2 Selector Program

## CC75

### Standard Features

Compressor – Gardner Denver Enduro 25

Driver – Cummins G5.9

Weight – 8,000lb / 3,625kg

Compressor Speed Optimization

### Options

- Easy 1 Controller
- Sound Proofing
- SCADA Output
- Blowcase
- Fire & Gas Detection



Phone: (403) 219-3026  
Fax: (403) 717-1759

#8, 1820 - 30th Ave. NE  
Calgary, Alberta Canada T2E 7M5

info@compactcompression.com